

UNISYS e-@ction THIN CLIENT TERMINAL WP3200

UNISYS



The Unisys Ultra Thin WP3200 is specifically designed for network users who need access to standard productivity applications like e-mail, the Internet, and network-based peripherals..



The WinPath WP 3200 is also the ideal desktop appliance for migrating legacy environments utilizing character terminals to Windows computing. The Ultra Thin WP3200 can easily be mounted under a desk, on a wall or even to the side of a monitor, making this ideal for saving desktop real estate.

The Unisys WP3200 is based on Microsoft's Windows CE, and supports connectivity through Microsoft's Remote Desktop Protocol and Citrix ICA technology to connect to Windows 2000 Server with Terminal Services enabled, Windows NT 4.0, Terminal Server Edition or Citrix MetaFrame servers via 10/100Base-T Ethernet connection. The WP3200 also comes standard with 15 local terminal emulations and includes a fully integrated 16-bit stereo sound capability, two USB ports.

Key Features

- ▶ Microsoft Windows CE for Windows-based terminals operating system
- ▶ Multiple terminal emulations standard
- ▶ Modular design connects to any VESA standard monitor
- ▶ Supports RDP and ICA 3 protocols
- ▶ Multiple session support
- ▶ Two USB ports
- ▶ 10/100BaseT Fast Ethernet
- ▶ Convection cooled; no moving parts
- ▶ Supports SNMP, DHCP, asset management
- ▶ Centrally managed and configurable
- ▶ One year standard depot warranty with Unisys Advanced Replacement and Repair Warranty

Key Benefits

- ▶ Industry-standard operating system
- ▶ Delivers simple integration of legacy systems with Windows 2000
- ▶ Freedom to choose the monitor that best suits your needs
- ▶ Gives administrators the flexibility to choose the protocol they need
- ▶ Increased productivity
- ▶ Convenient connection options
- ▶ Quiet, durable, reliable; low electricity use
- ▶ Works with all major industry-standard network management software packages
- ▶ Permits asset management, firmware upgrades, reconfiguration, and customized configurations either from administration server or from other desktops

The Unisys e-@ction Thin Client Terminal WP3000 series offers unparalleled features including seamless implementation of Windows NT-based transaction processing applications, multiple sessions, and multiple-protocol access to Windows and legacy applications, all based on the Windows CE operating system.

Administrators prefer these terminals because they can be set up and added to the network quickly using the simple setup wizard. And, with our terminal administrators are free to choose the protocol that best fits their needs. They can select an end-to-end Microsoft solution using the Remote Desktop (RDP) or take advantage of the Citrix ICA protocol through Citrix MetaFrame, or WinFrame server software.

The WP3200 modular Windows-based terminal is designed for users who have limited space, or want to match an existing or a new monitor to specific needs. These terminals have a tiny footprint, an attractive design, and can be wall mounted.

TECHNICAL SPECIFICATIONS

MODULAR WINDOWS-BASED TERMINAL

- ▶ Integrated Microsoft RDP and Citrix ICA 3 protocols and terminal personalities standard

DISPLAY SUPPORT¹

- ▶ VESA monitor support, with DDC for automatic setting of resolution and refresh rate
- ▶ Colors: 16 or 256
- ▶ Video: selectable, up to 1024x768, 8-bit color
- ▶ Flicker-free, 85 Hz non-interlaced refresh rate

AUDIO^{1, 2}

- ▶ Output: 1/8-inch mini, full 16-bit stereo, 44 KHz sample rate
- ▶ Input: 1/8-inch 8-bit mini microphone

INPUT/OUTPUT/PERIPHERAL SUPPORT

- ▶ Keyboard: enhanced USB with Windows keys (104 keys); low profile design with two-position tilt; detachable 5-foot (1.5-meter) cable³
- ▶ USB keyboards provide the connection for the mouse. KB10-US, United States; KB11-UK, United Kingdom; KB11-SP, Spain; KB11-GR, Germany; KB11-FR, France; KB11-IT, Italy.
- ▶ Mouse: PS/2 mouse included
- ▶ Local and/or network printers on ICA (virtual port redirection ready)
- ▶ VGA-type video output (DB-15)

NETWORKING

- ▶ TCP/IP with DNS and DHCP
- ▶ 10/100BaseT Fast Ethernet, twisted pair (RJ-45)
- ▶ Point-to-Point Protocol (PPP)
- ▶ Multiple master browser support on ICA supports Citrix load balancing on ICA
- ▶ SNMP support allows configuration of terminal settings, reporting of terminal configuration and attached devices, traps
- ▶ DHCP support for automatic firmware upgrades and unit configuration

COMMUNICATIONS

- ▶ Two USB Ports: One port dedicated for USB keyboard, one port unused, requires optional USB to serial/parallel [Digi Adapter] for local printing until USB print drivers are available.

COMMUNICATION PROTOCOLS/TERMINAL EMULATIONS SUPPORTED

- ▶ RDP resident
- ▶ ICA 3 resident
- ▶ Wyse WY-60, WY-50, WY-50+; IBM TN3270e, TN5250, 3151; DEC VT420; ADDS A2; Hazeltine 1500; and SCO Console resident

SERVER OS COMPATIBILITY/SUPPORT

- ▶ Microsoft Windows 2000
- ▶ Microsoft Windows NT Server 4.0, Terminal Server Edition
- ▶ Citrix WinFrame
- ▶ Citrix MetaFrame, the Citrix enhancement to Microsoft Windows NT Server 4.0, Terminal Server Edition

SET-UP AND CONFIGURATION

User Interface

- ▶ Local boot
- ▶ Start-up wizard for simple set-up
- ▶ Keyboard language support: Belgian Dutch and French, Brazilian, Canadian French, Danish, Dutch, Finnish, French, German, Italian, Norwegian, Portuguese, Spanish, Swedish, Swiss French, Swiss German, U.K. English, and U.S. English

Configuration

- ▶ Configurable automatic login
- ▶ Individual scripting

PHYSICAL CHARACTERISTICS

- ▶ Height: 1.70 inches (4.3cm)
- ▶ Width: 7.64 inches (19.4cm)
- ▶ Depth: 6.18 inches (15.7cm)
- ▶ Shipping weight: 7.7 lbs (3.5kg)
- ▶ Mounting bracket for installation beneath desk or on wall optional

ENVIRONMENTAL

Temperature range

- ▶ Powered on: 32° to 104°F (10° to 40°C)
- ▶ Powered off: -14° to 140°F (-10° to 60°C)
- ▶ Convection cooling, fanless design

Humidity

- ▶ 20% to 80% non-condensing

Operating altitude range

- ▶ 0 to 10,000 feet (0 to 3,050 meters)

POWER

- ▶ Worldwide auto-sensing 90-264 VAC, 47-63 Hz
- ▶ Energy saving automatic power-down

REGULATORY COMPLIANCE

Ergonomics

- ▶ German ZH1/618
- ▶ EN29241-3 approved
- ▶ EPA Energy Star

Safety

- ▶ UL 1950, CSA 950
- ▶ TÜV-GS approved
- ▶ EN60950 approved

RF interference

- ▶ FCC Class B pending
- ▶ CE mark
- ▶ EN55022B pending
- ▶ VCCI

WARRANTY

- ▶ One-year standard depot warranty (worldwide) with Unisys Advanced Replacement and Repair (Arrow) Warranty. The Arrow Warranty is free for one year in the U.S. only.

CUSTOMER SERVICE

- ▶ The Unisys Customer Service Center offers a wide array of services and programs. For more information, or for the nearest Unisys Service Center, call 1-800-448-1424, or visit our web site at www.unisysdirect.com

1 Monitor or speakers and microphone not included. 2 Requires support by server OS and protocol. 3 Keyboard not included.

Unisys is a registered trademark of Unisys Corporation. Other trade names are trademarks of registered trademarks of their respective holders.

Unisys reserves the right to change specifications without notice.

© 2000 Unisys Corporation

